



Battery holder JBH24

- quick and simple battery change
- suitable for battery sizes 2450 and 2477
- tape and reel version available



RoHS compliant



Pb free



REACH compliant



Conflict mineral free

ASSEMBLY	
JBH24 PCB version	
Tape and Reel	

SUITABLE FOR BATTERY TYPES	
Sony	CR2450
	CR2477
Renata	CR2450N
	CR2477N
Panasonic	CR2450
	CR2477

BATTERY CONTACTS	
Current rating	≤ 1A (short term load: ~ 30 sec.)
	≤ 100mA (continuous withstand)
Material	CuSn6
Contact surface	2µm Soft-Ni (99,96%)
Solder area	Ni solderable

HOLDING CONTACTS	
Material	CuZn37
Contact surface	Sn (lead free)

HOUSING	
Material	ULTRAMID T KR 4365 G5
	Melting point: 295°C
	Heat deflection temperature (1.8MPa): 270°C
	Combustibility: UL-V-2 (E41871)
Allowance	Masterbatch UN-MD0051

PROCESSING	
Manually	
Solder wave	
Reflow-soldering < 270°C (5 min. max.)	

FEATURES	
Suction area for automated placement	

MISCELLANEOUS	
All components and surfaces are RoHS-compliant according to directive 2002/95/EG.	

